

Raport Badawczy
Research Report

RB/95/2003

**Shape optimization
of thermoviscoelastic
contact problems**

A. Myśliński

Instytut Badań Systemowych
Polska Akademia Nauk

Systems Research Institute
Polish Academy of Sciences



Shape optimization of thermoviscoelastic contact problems

by

A. Myśliński

Systems Research Institute, Polish Academy of Sciences,
ul. Newelska 6, 01 - 447 Warsaw, Poland
e-mail: myslinsk@ibspan.waw.pl

Abstract: This paper is concerned with a shape optimization problem of a viscoelastic body in unilateral dynamic contact with a rigid foundation. The contact with Coulomb friction is assumed to occur at a portion of the boundary of the body. The nonpenetration condition is described in terms of velocities. The thermal deformation is taken into account. Using the material derivative method as well as the results concerning the regularity of solutions to dynamic variational thermoviscoelastic problem the directional derivative of the cost functional is calculated. A necessary optimality condition is formulated.

Keywords: dynamic thermoviscoelastic contact problem, shape optimization, sensitivity analysis, necessary optimality condition.

1. Introduction

This paper deals with the formulation of a necessary optimality condition for a shape optimization problem of a viscoelastic body in unilateral dynamic contact with a rigid foundation. The contact with a given friction, described by Coulomb law (Duvaut, Lions, 1972), is assumed to occur at a portion of the boundary of the body. The contact condition is described in terms of velocities. This first order approximation seems to be physically realistic for the case of a small distance between the body and the obstacle, and for small time intervals. The friction coefficient is assumed to be bounded. Since the friction represents significant heat source, heat generation and flow are taken into account. The equilibrium state of this thermoviscoelastic contact problem is described by a coupled hyperbolic - parabolic system. This system consists of an hyperbolic hemivariational inequality of the second order, governing a displacement field, and a parabolic equation governing a heat flow. The existence of solutions to dynamic hemivariational inequalities is shown in Goeleven, Miettinen, Panagiotopoulos (1999), Han, Sofonea (2002), Jarušek, Eck (1999), Jarušek (1996).

The existence of solutions to the coupled thermoviscoelastic contact problems is shown in Jarušek, Eck (1999) using the Schouder fixed - point theorem.

The shape optimization problem for a viscoelastic body in contact consists in finding, in a contact region, such shape of the boundary of the domain occupied by the body that the normal contact stress is minimized. It is assumed, that the volume of the body is constant.

Shape optimization of static contact problems was considered, among others, in Haslinger, Neittaanmäki (1988), Klabring, Haslinger (1993), Myśliński (1991, 1992, 1994), Sokołowski, Zolésio (1992). In Haslinger, Neittaanmäki (1988), Klabring, Haslinger (1993) the existence of optimal solutions and convergence of the finite-dimensional approximation was shown. Moreover, it was shown that optimal shape of the bodies in contact implies almost constant normal contact stress. In Myśliński (1991, 1992, 1994), Sokołowski, Zolésio (1992) the necessary optimality conditions were formulated using the material derivative approach (see Zolésio, 1992). Numerical results are reported in Haslinger, Neittaanmäki (1988), Myśliński (1994). The necessary optimality conditions for shape optimization problems of dynamic contact problems were formulated in Jarušek, Krbec, Rao, Sokołowski (2002), Myśliński (2000). In Jarušek, Krbec, Rao, Sokołowski (2002) the conical differentiability of solutions to parabolic variational inequality was shown. The material derivative approach was used in Myśliński (2000) to formulate a necessary optimality condition for the shape optimization problem of viscoelastic bodies in unilateral contact with a given friction. The shape optimization for thermoelastic problems was considered in Myśliński, Tröltzsch (1999). In this paper a necessary optimality condition was formulated for thermoelastic problem described by a coupled elliptic - parabolic system with a nonlinear boundary condition. The existence of solutions to optimal design problems for systems described by parabolic or hyperbolic variational inequalities was shown in Denkowski, Migórski (1998), Gasiński (2000).

In the present paper we study this shape optimization problem for a viscoelastic body in unilateral dynamical contact with friction and heat flow. Using material derivative method, Sokołowski, Zolésio (1992), as well as the results of regularity of solutions to the dynamic variational inequality, Jarušek, Eck (1999), Jarušek (1996), we calculate the directional derivative of the cost functional and we formulate a necessary optimality condition for this problem.

We shall use the following notation : $\Omega \subset R^2$ will denote a bounded domain with Lipschitz continuous boundary Γ . The time variable will be denoted by t and the time interval $I = (0, T), T > 0$. By $H^k(\Omega)$, $k \in (0, \infty)$, we will denote the Sobolev space of functions having derivatives in all directions of the order k belonging to $L^2(\Omega)$, Adams (1975). For an interval I and a Banach space B , $L^p(I; B)$, $p \in (1, \infty)$, denotes the usual Bochner space, Duvaut, Lions (1972). $\dot{u} = \frac{du}{dt}$ and $\ddot{u} = \frac{d^2u}{dt^2}$ will denote first and second order derivatives of function u with respect to t , respectively. \dot{u}_N and \dot{u}_T will denote normal and tangential components of function \dot{u} , respectively. $Q = I \times \Omega$, $\gamma_i = I \times \Gamma_i$, $i = 1, 2, 3$,

where Γ_i are disjoint pieces of the boundary Γ .

2. Contact problem formulation

Consider deformations of an elastic body occupying domain $\Omega \subset R^2$. The boundary Γ of domain Ω is Lipschitz continuous. The body is subject to body forces $f = (f_1, f_2)$. Moreover, surface tractions $p = (p_1, p_2)$ are applied to a portion Γ_1 of the boundary Γ . We assume that the body is clamped along the portion Γ_0 of the boundary Γ . The contact conditions are prescribed on the portion Γ_2 of the boundary Γ . Moreover $\Gamma_i \cap \Gamma_j = \emptyset$, $i \neq j$, $i, j = 0, 1, 2$, $\Gamma = \Gamma_0 \cup \Gamma_1 \cup \Gamma_2$.

We denote by $u = (u_1, u_2)$, $u = u(t, x)$, $t \in [0, T]$, $0 < T < \infty$, $x \in \Omega$, a displacement of the body and by $\theta = \theta(t, x)$ an absolute temperature of the strip. $\sigma = \{\sigma_{ij}(u(t, x))\}$, $i, j = 1, 2$, denotes the stress field in the body. We shall consider viscoelastic bodies obeying the Kelvin-Voigt law, Duvaut, Lions (1972), Haslinger, Neittaanmäki (1988), Hlavacek et al. (1986), Telega (1987):

$$\begin{aligned}\sigma_{ij}(u(t, x)) &= c_{ijkl}^0(x)e_{kl}(u) + c_{ijkl}^1(x)e_{kl}(\dot{u}) \quad x \in \Omega, \\ e_{kl} &= \frac{1}{2}(u_{k,l} + u_{l,k}),\end{aligned}\tag{1}$$

$i, j, k, l = 1, 2$, $u_{k,l} = \frac{\partial u_k}{\partial x_l}$. We use here the summation convention over repeated indices, Duvaut, Lions (1972). $c_{ijkl}^0(x)$ and $c_{ijkl}^1(x)$, $i, j, k, l = 1, 2$, are components of Hook's tensor. It is assumed that the elasticity coefficients c_{ijkl}^0 and c_{ijkl}^1 are Lipschitz continuous with respect to the space variable. Moreover, they satisfy usual symmetry, boundedness and ellipticity conditions, Duvaut, Lions (1972), Jarušek (1999), Haslinger, Neittaanmäki (1988), Halvacek et al. (1986), Jarušek, Eck (1999) i.e.,

$$c_{ijkl}^l(x) = c_{jikl}^l(x) = c_{klij}^l(x),\tag{2}$$

$$m_0^l \xi_{ij} \xi_{kl} \leq c_{ijkl}^l(x) \xi_{ij} \xi_{kl} \leq M_0^l \xi_{ij} \xi_{kl},\tag{3}$$

for all symmetric second order tensors ξ_{ij} and all $x \in \Omega$ with constants $0 < m_0^l \leq M_0^l$, $l = 0, 1$.

In an equilibrium state a stress field σ and a temperature field θ satisfy the system, Duvaut, Lions (1972), Haslinger, Neittaanmäki (1988), Jarušek, Eck (1999), Jarušek (1996), of equations:

$$\ddot{u}_i - \sigma_{ij}(u(t, x))_{,j} = f_i(x) + (b_{ij}\theta)_{,j} \quad \text{in } (0, T) \times \Omega, \quad i, j = 1, 2,\tag{4}$$

where $\sigma_{ij}(u(t, x))_{,j} = \frac{\partial \sigma_{ij}(u(t, x))}{\partial x_j}$, $i, j = 1, 2$. b_{ij} , $i, j = 1, 2$, denotes a thermal expansion tensor, symmetric, bounded, elliptic and Lipschitz continuous with respect to the space variable. The temperature flow is governed by:

$$\dot{\theta} - (c_{ij}\theta_{,j})_{,i} + b_{ij}^1 \dot{u}_{i,j} = 0 \quad \text{in } (0, T) \times \Omega,\tag{5}$$

where c_{ij} , $i, j = 1, 2$, is a tensor of thermal conductivity, Lipschitz continuous with respect to the space variable and satisfying usual symmetry, boundedness and ellipticity conditions. b_{ij}^1 , $i, j = 1, 2$, denotes a thermal deformation tensor, symmetric, bounded, elliptic and Lipschitz continuous with respect to the space variable. The dependance of this tensor on current temperature is neglected. The following initial conditions are given

$$u_i(0, x) = u_0, \quad \text{and} \quad \dot{u}_i(0, x) = u_1, \quad i = 1, 2, \quad \text{in } \Omega, \quad (6)$$

$$\theta(0, x) = \theta_0 \quad \text{in } \Omega. \quad (7)$$

u_0, u_1, θ_0 are given functions. The following boundary conditions are given

$$\begin{aligned} u_i(x) &= 0 \quad \text{on } (0, T) \times \Gamma_0, \quad i = 1, 2, \\ \sigma_{ij}(u)n_j &= p_i \quad \text{on } (0, T) \times \Gamma_1, \quad i, j = 2, \end{aligned} \quad (8)$$

$$\dot{u}_N \leq 0, \quad \sigma_N \leq 0, \quad \dot{u}_N \sigma_N = 0, \quad \text{on } (0, T) \times \Gamma_2, \quad (9)$$

$$\begin{aligned} \dot{u}_T = 0 &\Rightarrow |\sigma_T| \leq \mathcal{F} |\sigma_N|, \\ \dot{u}_T \neq 0 &\Rightarrow \sigma_T = -\mathcal{F} |\sigma_N| \frac{\dot{u}_T}{|\dot{u}_T|} \quad \text{on } (0, T) \times \Gamma_2. \end{aligned} \quad (10)$$

Here we use the notation: $u_N = u_i n_i$, $\sigma_N = \sigma_{ij} n_i n_j$, $(u_T)_i = u_i - u_N n_i$, $(\sigma_T)_i = \sigma_{ij} n_j - \sigma_N n_i$, $i, j = 1, 2$, where $n = (n_1, n_2)$ is the unit outward versor to the boundary Γ . \mathcal{F} denotes the friction coefficient. Moreover, the heat flux on the boundary of the strip Ω is equal to:

$$\frac{\partial \theta}{\partial n}(t, x) = \kappa(\theta_g - \theta), \quad \text{on } (0, T) \times (\Gamma_0 \cup \Gamma_1), \quad (11)$$

$$\frac{\partial \theta}{\partial n}(t, x) = \kappa(\theta_g - \theta) + \mathcal{F} |\sigma_N| |\dot{u}_T|, \quad \text{on } (0, T) \times \Gamma_2. \quad (12)$$

κ is a given nonnegative, bounded, measurable function of the space variable and θ_g is a given external temperature. Since for $u \rightarrow \infty$ the term describing the frictional heat generation may increase faster than all the other terms, it creates the main difficulty in the investigation of the coupled problem. To assure the existence of solutions to the problem (1)–(12), we replace the frictional heat generation term $\mathcal{F} |\sigma_N| |\dot{u}_T|$ by a function $j(x, \mathcal{F} |\sigma_N|, |\dot{u}_T|)$. This function is assumed monotone in the second and third argument and satisfying the linear growth condition

$$j(x, \mathcal{F} |\sigma_N|, |\dot{u}_T|) \leq \text{const}_1 (1 + \mathcal{F} |\sigma_N| + |\dot{u}_T|), \quad (13)$$

with some positive constant $\text{const}_1 \in R$. Moreover, for $g_n \rightarrow g$ in $L^2(\Gamma_2)$ and $h_n \rightarrow h$ in $L^2(\Gamma_2)$ the function j satisfies for a.e. $x \in \Omega$

$$j(\cdot, g_n, h_n) \rightarrow j(\cdot, g, h) \quad \text{in } L^\alpha(\Gamma_2), \quad \text{for } \alpha > \frac{8}{5}. \quad (14)$$

We shall consider problem (4)–(12) in the variational form. Let us assume,

$$\begin{aligned}
 & f \in H^{1/4}(I; (H^1(\Omega; R^2))^* \cap L^2(I; (H^{1/2}(\Omega; R^2))^*)), \\
 & p \in L^2(I; (H^{-1/2}(\Gamma_1; R^2))), \quad u_0 \in H^{3/2}(\Omega; R^2), \quad u_1 \in H^{3/2}(\Omega; R^2), \\
 & \theta_0 \in L^2(\Omega; R), \quad \theta_g \in L^2(I; H^{-1/2}(\Gamma; R)), \\
 & \mathcal{F} \geq 0, \quad \mathcal{F} \in L^\infty(\Gamma_2; R^2), \quad \mathcal{F}(\cdot, x) \text{ is continuous for a. e. } x \in \Gamma_2,
 \end{aligned}
 \tag{15}$$

are given. The compatibility conditions $u_0|_{\Gamma_0 \cup \Gamma_2} = 0, u_1|_{\Gamma_0} = 0$ are assumed to be satisfied. The space $L^2(Q; R^2)$ and the Sobolev spaces $H^{1/4}(I; (H^1(\Omega; R^2))^*)$ as well as $(H^{1/2}(\Gamma_1); R^2)$ are defined in Adams (1975), Duvaut, Lions (1972). Let us introduce:

$$H = H^{1/2}(I; H^1(\Omega; R^2)), \quad F = \{z \in H : z_i = 0 \text{ on } (0, T) \times \Gamma_0, i = 1, 2\}, \tag{16}$$

$$K = \{ \in F : \dot{z}_N \leq 0 \text{ on } (0, T) \times \Gamma_2 \}. \tag{17}$$

Let us also introduce the bilinear forms: $a^i(\cdot, \cdot) : F \times F \rightarrow R, i = 0, 1$, given by

$$\begin{aligned}
 a^0(u, v) &= \int_Q c_{ijkl}^0 e_{ij}(u) e_{kl}(v) dxdt, \\
 a^1(u, v) &= \int_Q c_{ijkl}^1 e_{ij}(u) e_{kl}(v) dxdt.
 \end{aligned}
 \tag{18}$$

The problem (1)–(12) is equivalent to the following variational problem, Jarušek, Eck (1999), Jarušek (1996): find a pair (u, θ) , such that $u \in L^2(I; H^1(\Omega; R^2)) \cap H^{1/2}(I; H^1(\Omega; R^2)) \cap K, \dot{u} \in L^2(I; H^1(\Omega; R^2)) \cap H^{1/2}(I; L^2(\Omega; R^2)) \cap K$, and $\ddot{u} \in L^2(I; H^{-1}(\Omega; R^2)) \cap (H^{1/2}(I; L^2(\Omega; R^2)))^*, \theta \in H^{1/2,1}(Q), \dot{\theta} \in (H^{1/2,1}(Q))^*$ satisfying the initial conditions (6)–(7) as well as the following system, Jarušek, Eck (1999), Jarušek (1996),

$$\begin{aligned}
 & \int_Q \ddot{u}(v - \dot{u}) dxdt + a^0(u, v - \dot{u}) + a^1(\dot{u}, v - \dot{u}) - \int_Q b_{ij} \theta e_{ij}(v - \dot{u}) dxdt + \\
 & \int_0^T \int_{\Gamma_2} j(\mu | \sigma_N |, (| v_T | - | \dot{u}_T |)) dsdt \geq \\
 & \int_Q f v dxdt + \int_{\gamma_2} p v dsdt \quad \forall v \in K,
 \end{aligned}
 \tag{19}$$

$$\begin{aligned}
 & \int_Q \dot{\theta} \varphi dxdt + \int_Q (c_{ij} \theta_{,j} \varphi_{,i} + b_{ij}^1 \dot{u}_{i,j} \varphi) dxdt + \int_0^T \int_{\Gamma} \kappa(\theta_g - \theta) \varphi dsdt = \\
 & \int_0^T \int_{\Gamma_2} j(\mu | \sigma_N |, | \dot{u}_T |) \varphi dsdt \quad \forall \varphi \in H.
 \end{aligned}
 \tag{20}$$

The existence of solutions to system (19)–(20) was shown in Jarušek, Eck (1999).

THEOREM 2.1 *Assume : (i) the data are smooth enough, i.e. (13), (14), (15) are satisfied (ii) Γ_2 is of class $C^{1,1}$ (iii) the friction coefficient is small enough. Then there exists a solution to the problem (19)–(20).*

Proof. The proof is based on the fixed point theorem of Schouder and is given in Jarušek, Eck (1999). First, for a given temperature field $\bar{\theta}$, a unique solution u to the contact problem (19) is shown to exist. The proof consists in penalization of the inequality (19), friction regularization and employment of localization and shifting technique due to Lions and Magenes (see Jarušek, 1996). Next, for the found displacement $u(\bar{\theta})$, the existence of a unique temperature field $\theta(u(\bar{\theta}))$ satisfying the heat equation (20) is proved. This procedure defines an operator $\Phi : \bar{\theta} \rightarrow \theta$. Since the operator Φ maps an appropriate convex bounded set into itself and is completely continuous it implies the existence of a fixed point of this operator as well as the existence of a solution to the thermoviscoelastic contact problem (19)–(20). ■

We confine ourselves to consideration of the contact problem with a prescribed friction, i.e.,

$$\mathcal{F} | \sigma_N | = \sigma_T \leq 1. \quad (21)$$

The condition (10) is replaced by the following one,

$$\dot{u}_T \sigma_T + | \dot{u}_T | = 0, \quad | \sigma_T | \leq 1 \quad \text{on } I \times \Gamma_2. \quad (22)$$

For the sake of simplicity we set $c_{ij} = 1$, $i, j = 1, 2$, in (5). We shall consider the temperature flow governing equation (5) with $b_{ij}^1 = 0$, $i, j = 1, 2$. Moreover, we assume, that the boundary condition (12) does not contain the term depending on a friction coefficient, i.e., it has the form

$$\frac{\partial \theta}{\partial n}(t, x) = \kappa(\theta_g - \theta) + g(\theta, t, x), \quad \text{on } (0, T) \times \Gamma_2. \quad (23)$$

Let $\hat{\Omega} \subset R^2$ be a domain such that $\Omega \subset \hat{\Omega}$. We assume that $g(.,.,.) : R \times [0, T] \times \hat{\Omega} \rightarrow R$ satisfies the following assumptions, Myśliński, Tröltzsch (1999):

- (A1) $g(.,.,.)$ is continuously differentiable w.r. to (θ, t, x)
 $| g(0, t, x) | \leq \psi_0 \forall (t, x) \in [0, T] \times \hat{\Omega}$
 $| g_\theta(\theta, t, x) | + | g_t(\theta, t, x) | \leq \psi_M \forall (\theta, t, x)$
 $\in [-M, M] \times [0, T] \times \hat{\Omega}$
 here, ψ_0 and ψ_M are certain real constants. (24)
- (A2) $g_\theta(\theta, t, x) \leq 0 \forall (\theta, t, x) \in R \times [0, T] \times \hat{\Omega}$
- (A3) Compatibility conditions: $\theta_0(x) = \theta_0$
 is constant on $\hat{\Omega}$ and $g(\theta_0(x), 0, x) = 0$.

$g_\theta(\theta, t, x)$ denotes the derivative of function g with respect to θ . By introducing a set

$$\Lambda = \{\lambda \in L^2(I; L^\infty(\Gamma_2; R^2)) : |\lambda| \leq 1 \text{ on } I \times \Gamma_2\}, \tag{25}$$

and taking into account (22), (23) we transform the system (20)–(21) into : find $u \in K$, $\lambda \in \Lambda$ and $\theta \in H$ such that,

$$\int_Q \ddot{u}(v - \dot{u}) dxdt + a^0(u, v - \dot{u}) + a^1(\dot{u}, v - \dot{u}) - \int_Q b_{ij} \theta e_{ij}(v - \dot{u}) dxdt - \int_{\gamma_2} \lambda_T (v_T - \dot{u}_T) dx d\tau \geq \int_Q f v dxdt + \int_{\gamma_2} p v dxdt \quad \forall v \in K, \tag{26}$$

$$\int_{\gamma_2} \sigma_T \dot{u}_T ds d\tau \leq \int_{\gamma_2} \lambda_T \dot{u}_T ds d\tau \quad \forall \lambda_T \in \Lambda, \tag{27}$$

$$\int_Q \dot{\theta} \varphi dxdt + \int_Q \theta_{,j} \varphi_{,i} dxdt + \int_0^T \int_{\Gamma_0 \cup \Gamma_1} \kappa(\theta_g - \theta) \varphi dsdt + \int_0^T \int_{\Gamma_2} (\kappa(\theta_g - \theta) + g(\theta, t, x)) \varphi dsdt = 0 \quad \forall \varphi \in H. \tag{28}$$

3. Formulation of the shape optimization problem

We are going to consider a family $\{\Omega_s\}$ of the domains Ω_s depending on parameter s . For each Ω_s we formulate a variational problem corresponding to (26)–(28). In this way we obtain a family of the variational problems depending on s and for this family we shall study a shape optimization problem, i.e., we minimize with respect to s a cost functional associated with the solutions to (26)–(28).

We shall consider the domain Ω_s as an image of a reference domain Ω under a smooth mapping \mathbf{T}_s . To describe the transformation \mathbf{T}_s we shall use the speed method Sokolowski, Zolésio (1992). Let us denote by $V(s, x)$ the sufficiently regular vector field depending on parameter $s \in [0, \vartheta]$, $\vartheta > 0$:

$$V(., .) : [0, \vartheta] \times R^2 \rightarrow R^2, \\ V(s, .) \in C^2(R^2, R^2) \quad \forall s \in [0, \vartheta], \quad V(., x) \in C([0, \vartheta], R^2) \quad \forall x \in R^2. \tag{29}$$

Let $\mathbf{T}_s(V)$ denote the family of mappings: $\mathbf{T}_s(V) : R^2 \ni X \rightarrow x(t, X) \in R^2$ where the vector function $x(., X) = x(.)$ satisfies the system of ordinary differential equations:

$$\frac{d}{d\tau} x(\tau, X) = V(\tau, x(\tau, X)), \tau \in [0, \vartheta], \quad x(0, X) = X \in R. \tag{30}$$

We denote by DT_s the Jacobian of the mapping $T_s(V)$ at a point $X \in R^2$. We denote by DT_s^{-1} and ${}^*DT_s^{-1}$ the inverse and the transpose inverse of the Jacobian DT_s , respectively. $J_s = \det DT_s$ will denote the determinant of the Jacobian DT_s . The family of domains $\{\Omega_s\}$ depending on parameter $s \in [0, \vartheta]$, $\vartheta > 0$, is defined as follows: $\Omega_0 = \Omega$,

$$\begin{aligned} \Omega_s &= T_s(\Omega)(V) = \{x \in R^2 : \exists X \in R^2 \\ &\text{such that, } x = x(s, X), \text{ where the function } x(\cdot, X) \text{ satisfies} \\ &\text{equation (30) for } 0 \leq \tau \leq s \}. \end{aligned} \tag{31}$$

Let us consider problem (26)–(28) in the domain Ω_s . Let F_s, K_s, Λ_s be defined, by (16), (17), (23), respectively, with Ω_s instead of Ω . We shall write $u_s = u(\Omega_s)$, $\sigma_s = \sigma(\Omega_s)$ and $\theta_s = \theta(\Omega_s)$. The problem (26)–(28) in the domain Ω_s takes the form: find $u_s \in K_s, \lambda_s \in \Lambda_s$ and $\theta_s \in H_s$ such that

$$\begin{aligned} \int_{Q_s} \dot{u}_s(v - \dot{u}_s) dxdt + a^0(u_s, v - \dot{u}_s) + a^1(\dot{u}_s, v - \dot{u}_s) - \\ \int_{Q_s} b_{ij} \theta_s e_{ij}(v - \dot{u}_s) dxdt - \int_{\gamma_{s2}} \lambda_{Ts}(v_T - \dot{u}_{Ts}) dxdt \geq \\ \int_{Q_s} f v dxdt + \int_{\gamma_{s2}} p v dxdt \quad \forall v \in H^{1/2}(I; H^1(\Omega_s; R^2)) \cap K, \end{aligned} \tag{32}$$

$$\int_{\gamma_{s2}} \sigma_{sT} \dot{u}_{sT} dsd\tau \leq \int_{\gamma_{s2}} \lambda_{sT} \dot{u}_{sT} dsd\tau \quad \forall \lambda_{sT} \in \Lambda_s, \tag{33}$$

$$\begin{aligned} \dot{\theta}_s \varphi dxdt + \int_{Q_s} \theta_{s,j} \varphi_{,i} dxdt + \int_0^T \int_{\Gamma_{s0} \cup \Gamma_{s1}} \kappa(\theta_g - \theta) dsdt + \\ \int_0^T \int_{\Gamma_{s2}} (\kappa(\theta_g - \theta_s) + g(\theta_s, t, x)) \varphi dsdt = 0 \quad \forall \varphi \in H_s. \end{aligned} \tag{34}$$

Let us formulate the optimization problem. By $\hat{\Omega} \subset R^2$ we denote a domain such that $\Omega_s \subset \hat{\Omega}$ for all $s \in [0, \vartheta]$, $\vartheta > 0$. Let $\phi \in M$ be a given function. The set M is determined by

$$M = \{\phi \in L^\infty(I; H_0^2(\hat{\Omega}; R^2)) : \phi \leq 0 \text{ on } I \times \hat{\Omega}, \|\phi\|_{L^\infty(I; H_0^2(\hat{\Omega}; R^2))} \leq 1\}. \tag{35}$$

Let us introduce, for given $\phi \in M$, the following cost functional:

$$J_\phi(u_s) = \int_{\gamma_{s2}} \sigma_{sN} \phi_s N dzd\tau, \tag{36}$$

where ϕ_{sN} and σ_{sN} are normal components of ϕ_s and σ_s , respectively, depending on parameter s . Note that the cost functional (36) approximates the normal contact stress, Haslinger, Neittaanmäki (1988), Klöppel, Haslinger (1993), Myśliński (1994). We shall consider a such family of domains $\{\Omega_s\}$ that every Ω_s , $s \in [0, \vartheta]$, $\vartheta > 0$, has constant volume $c > 0$, i.e., every Ω_s belongs to the constraint set U given by

$$U = \{\Omega_s : \int_{\Omega_s} dx = c\}. \quad (37)$$

We shall consider the following shape optimization problem:

$$\begin{aligned} &\text{For given } \phi \in M, \text{ find the boundary } \Gamma_{2s} \text{ of the domain } \Omega_s \\ &\text{occupied by the body, minimizing the cost functional (36)} \\ &\text{subject to } \Omega_s \in U. \end{aligned} \quad (38)$$

The set U given by (37) is assumed to be nonempty. $(u_s, \lambda_s, \theta_s) \in K_s \times \Lambda_s \times H_s$ satisfy (32)–(34). Note that the goal of the shape optimization problem (38) is to find such boundary Γ_2 of the domain Ω occupied by the body that the normal contact stress is minimized. Remark, that the cost functional (36) can be written in the following form, Haslinger, Neittaanmäki (1988), Telega (1987):

$$\begin{aligned} \int_{\gamma_{s2}} \sigma_{sN} \phi_{sN} ds d\tau &= \int_{Q_s} \ddot{u}_s \phi_s dx d\tau + \int_{Q_s} \sigma_{sij}(u_s) e_{kl}(\phi_s) dx d\tau - \\ &\int_{Q_s} f \phi_s dx d\tau - \int_{Q_s} b_{ij} \theta_s e_{ij}(\phi_s) dx d\tau - \\ &\int_{\gamma_{s1}} p_s \phi_s dz d\tau - \int_{\gamma_{s2}} \sigma_{sT} \phi_{sT} dz d\tau. \end{aligned} \quad (39)$$

We shall assume that there exists at least one solution to the optimization problem (38). It implies the compactness assumption for the set (37) in a suitable topology. For detailed discussion concerning the conditions assuring the existence of optimal solutions see Haslinger, Neittaanmäki (1988), Sokółowski, Zolésio (1992).

4. Shape derivatives of contact problem solution

In order to calculate the Euler derivative (see Sokółowski, Zolésio, 1992) of the cost functional (36) we have to determine the shape derivatives (u', λ', θ') $\in F \times \Lambda \times H$ of a solution $(u_s, \lambda_s, \theta_s) \in K_s \times \Lambda_s \times H_s$ of the system (32)–(34). Let us recall from Sokółowski, Zolésio (1992):

DEFINITION 4.1 *The shape derivative $u' \in F$ of the function $u_s \in F_s$ is determined by:*

$$(\tilde{u}_s)|_{\Omega} = u + su' + o(s), \quad (40)$$

where $\|o(s)\|_F / s \rightarrow 0$ for $s \rightarrow 0$, $u = u_0 \in F$, $\tilde{u}_s \in F(R^2)$ is an extension of the function $u_s \in F_s$ into the space $F(R^2)$. $F(R^2)$ is defined by (10) with R^2 instead of Ω .

In order to calculate the shape derivatives $(u', \lambda', \theta') \in F \times \Lambda \times H$ of a solution $(u_s, \lambda_s, \theta_s) \in K_s \times \Lambda_s \times H_s$ of the system (32)–(34), first we calculate the material derivatives $(u^\bullet, \lambda^\bullet, \theta^\bullet) \in F \times \Lambda \times H$ of the solution $(u_s, \lambda_s, \theta_s) \in K_s \times \Lambda_s \times H_s$ to the system (32)–(34). Let us recall the notion of material derivative, Sokołowski, Zolésio (1992):

DEFINITION 4.2 *The material derivative $u^\bullet \in F$ of the function $u_s \in K_s$ at a point $X \in \Omega$ is determined by:*

$$\lim_{s \rightarrow 0} \|(u_s \circ \mathbf{T}_s) - u\|_F / s - u^\bullet = 0, \tag{41}$$

where $u \in K$, $u_s \circ \mathbf{T}_s \in K$ is an image of function $u_s \in K_s$ in the space F under the mapping \mathbf{T}_s .

Taking into account Definition 4.2 we can calculate material derivatives of a solution to the system (32)–(34):

LEMMA 4.1 *The material derivatives $(u^\bullet, \lambda^\bullet, \theta^\bullet) \in K_1 \times \Lambda \times H$ of a solution $(u_s, \lambda_s, \theta_s) \in K_s \times \Lambda_s \times H_s$ to the system (32)–(34) are determined as a unique solution to the following system:*

$$\begin{aligned} & \int_Q \{ \ddot{u}^\bullet \eta + \ddot{u} \eta^\bullet + \ddot{u} \eta \operatorname{div} V(0) + \sigma_{ij}(u^\bullet) e_{kl}(\eta) + \sigma_{ij}(u) e_{kl}(\eta^\bullet) - \\ & \sigma_{ij}(u) [{}^T DV(0) D\eta + DV(0) {}^T D\eta] - \sigma_{ij}(\eta) [{}^T DV(0) Du + DV(0) {}^T Du] - \\ & f^\bullet \eta - f \eta^\bullet + (\sigma_{ij}(u) e_{kl}(\eta) - f \eta) \operatorname{div} V(0) \} dx d\tau - \\ & \int_Q [b_{ij} \theta^\bullet e_{ij}(\eta) + b_{ij} \theta e_{ij}(\eta^\bullet) - b_{ij} \theta [{}^T DV(0) D\eta + DV(0) {}^T D\eta] + \\ & b_{ij} \theta e_{ij}(\eta) \operatorname{div} V(0)] dx d\tau - \\ & \int_{\gamma_1} (p^\bullet \eta + p \eta^\bullet + p \eta D) dx d\tau - \int_{\gamma_2} \{ \lambda^\bullet \eta_T + \lambda \eta_T^\bullet + \lambda \eta_T D \} dx d\tau \geq 0 \end{aligned} \tag{42}$$

$\forall \eta \in K_1,$

$$\int_{\gamma_2} [(\lambda^\bullet - \mu) \dot{u}_T + (\lambda - \mu^\bullet) \dot{u}_T + (\lambda - \mu) \dot{u}_T^\bullet + (\lambda - \mu) \dot{u}_T D] dx d\tau \geq 0 \tag{43}$$

$\forall \mu \in L_1,$

$$\begin{aligned}
 & \int_0^T \int_{\Omega} \{ [-\theta^\bullet \frac{\partial \varphi}{\partial t} - \theta \frac{\partial \varphi^\bullet}{\partial t} \operatorname{div} V(0)] + [\nabla \theta^\bullet \nabla \varphi + \\
 & \quad \nabla \theta \nabla \varphi^\bullet] + [\operatorname{div} V(0)I - ({}^T DV(0) + DV(0))\nabla \theta \nabla \varphi] \} dx dt = \\
 & \int_0^T \int_{\Gamma} \{ \frac{\partial g}{\partial \theta} \theta^\bullet \varphi + g \nabla \varphi V(0) + \nabla g \varphi V(0) + \\
 & \quad g \varphi (\operatorname{div} V(0) - (DV n, n)) \} dz dt + \int_{\Omega} \theta_0 \varphi(x, 0) \operatorname{div} V(0) dx \quad \forall \varphi \in H,
 \end{aligned} \tag{44}$$

where $V(0) = V(0, X)$, $DV(0)$ denotes the Jacobian matrix of the matrix $V(0)$ and div denotes a divergence operator. Moreover

$$\begin{aligned}
 K_1 = \{ \xi \in F : \xi = u - DVu \text{ on } \gamma_0, \xi n \geq n DV(0)u \text{ on } A_1, \\
 \xi n = n DV(0)u \text{ on } A_2 \},
 \end{aligned} \tag{45}$$

$$\begin{aligned}
 A_0 = \{ x \in \gamma_2 : \dot{u}_N = 0 \}, \quad A_1 = \{ x \in B : \sigma_N = 0 \}, \\
 A_2 = \{ x \in B : \sigma_N < 0 \},
 \end{aligned} \tag{46}$$

$$\begin{aligned}
 B_0 = \{ x \in \gamma_2 : \lambda_T = 1, \dot{u}_T \neq 0 \}, \\
 B_1 = \{ x \in \gamma_2 : \lambda_T = -1, \dot{u}_T = 0 \},
 \end{aligned} \tag{47}$$

$$\begin{aligned}
 B_2 = \{ x \in \gamma_2 : \lambda_T = 1, \dot{u}_T = 0 \}, \\
 L_1 = \{ \xi \in \Lambda : \xi \geq 0 \text{ on } B_2, \xi \leq 0 \text{ on } B_1, \xi = 0 \text{ on } B_0 \},
 \end{aligned} \tag{48}$$

and D is given by

$$D = \operatorname{div} V(0) - (DV(0)n, n). \tag{49}$$

Proof. The proof is based on approach proposed in Sokołowski, Zolésio (1992). First we transport the system (32)–(34) to the fixed domain Ω . Let $u^s = u_s \circ \mathbf{T}_s \in F$, $u = u_0 \in F$, $\lambda^s = \lambda_s \circ \mathbf{T}_s \in \Lambda$, $\lambda = \lambda_0 \in \Lambda$. Since in general $u^s \notin K(\Omega)$, we introduce a new variable $z^s = D\mathbf{T}_s^{-1}u^s \in K$. Moreover, $\dot{z} = \dot{u} - DV(0)u$, Jarušek (1996), Sokołowski, Zolésio (1988). Using this new variable z^s as well as the formulae for transformation of the function and its gradient into reference domain Ω , Sokołowski, Zolésio (1988, 1992), we write the system (32)–(34) in the reference domain Ω . Using the estimates on time derivative of function u , Jarušek (1996), the Lipschitz continuity of u , λ and θ satisfying (32)–(34) with respect to s can be proved. Applying to this system the result concerning the differentiability of solutions to variational inequality, Sokołowski, Zolésio (1988, 1992), we can expect that the material derivative $(u^\bullet, \lambda^\bullet, \theta^\bullet) \in K_1 \times \Lambda \times H$ satisfies the system (42)–(44). Moreover, from the ellipticity condition of the elasticity coefficients by a standard argument, Sokołowski, Zolésio (1988), it follows that $(u^\bullet, \lambda^\bullet, \theta^\bullet) \in K_1 \times \Lambda \times H$ is a unique solution to the system (42)–(44). ■

Recall, Sokółowski, Zolésio (1992), that if the shape derivative $u' \in F$ of the function $u_s \in F_s$ exists, then the following condition holds:

$$u' = u^\bullet - \nabla u V(0). \quad (50)$$

From the regularity result in Jarušek (1996), Myśliński, Tröltzsch (1999), it follows that:

$$\nabla u V(0) \in F, \quad \nabla \lambda_T V(0) \in \Lambda, \quad \nabla \theta V(0) \in H, \quad (51)$$

where the spaces F, H and L are determined by (16) and (23), respectively. Integration by parts of the system (42) - (44), and consideration of (50), (51), lead to a similar system to (42) - (44), determining the shape derivative $(u', \lambda'_T, \theta') \in F \times L \times H$ of the solution $(u_s, \lambda_{sT}, \theta_s) \in K_s \times L_s \times H_s$ of the system (32)-(34):

$$\begin{aligned} & \int_Q [\ddot{u}'\eta + \ddot{u}\eta' + (DV(0) + {}^T DV(0))\ddot{u}\eta] dx d\tau + \int_\gamma \ddot{u}\eta V(0) n ds d\tau + \\ & \int_Q \sigma_{ij}(u') e_{kl} \eta dx d\tau - \int_Q [b_{ij} \theta' e_{ij}(\eta) + b_{ij} \nabla \theta V(0) e_{ij}(\eta')] dx d\tau + \\ & \int_{\gamma_2} \{\lambda' \dot{\eta}_T + \lambda \dot{\eta}'_T\} dx d\tau + I_1(\dot{u}, \eta) + I_2(\lambda, u, \eta) \geq 0 \quad \forall \eta \in N_1, \end{aligned} \quad (52)$$

$$\int_{\gamma_2} [\dot{u}'_T(\mu - \lambda) - \dot{u}_T \lambda'] dx d\tau + I_3(u, \mu - \lambda) \geq 0 \quad \forall \mu \in L_1, \quad (53)$$

$$\begin{aligned} & \int_0^T \int_\Omega \{-\theta' \frac{\partial \varphi}{\partial t} + \nabla \theta' \nabla \varphi\} dx d\tau + \\ & \int_0^T \int_\Gamma \{\theta \frac{\partial \varphi}{\partial t} V(0) n + \nabla \theta \nabla \varphi V(0) n\} ds d\tau = 0, \end{aligned} \quad (54)$$

$$N_1 = \{\eta \in F : \eta = \lambda - DuV(0), \quad \lambda \in K_1\}, \quad (55)$$

$$\begin{aligned} I_1(\varphi, \phi) = & \int_\gamma \{\sigma_{ij}(\varphi) e_{kl} \phi - f \phi - \\ & ((\nabla p n) \phi + (p \nabla \phi) n + p \phi H) V(0) n\} dx d\tau, \end{aligned} \quad (56)$$

$$\begin{aligned} I_2(\mu, \varphi, \phi) = & \int_{\gamma_2} \{(\nabla \mu) n \nabla \phi + \mu (\nabla (\nabla \varphi n)) \varphi + \\ & \mu \nabla \dot{\varphi}_T H + \mu \nabla \varphi n\} V(0) n dx d\tau, \end{aligned} \quad (57)$$

$$\begin{aligned}
 I_3(\varphi, \mu - \lambda) = & \int_{\gamma_2} (\varphi n)(\mu - \lambda) + \varphi(\nabla \mu n) - \varphi(\nabla \lambda n) + \\
 & \varphi(\mu - \lambda)\tilde{H}]V(0)ndxd\tau,
 \end{aligned}
 \tag{58}$$

where \tilde{H} denotes the mean curvature of the boundary Γ , Sokolowski, Zolésio (1992).

5. Necessary optimality condition

Our goal is to calculate the directional derivative of the cost functional (36) with respect to the parameter s . We will use this derivative to formulate necessary optimality condition for the optimization problem (38). First, let us recall from Sokolowski, Zolésio (1992) the notion of Euler derivative of the cost functional depending on domain Ω :

DEFINITION 5.1 *Euler derivative $dJ(\Omega; V)$ of the cost functional J at a point Ω in the direction of the vector field V is given by:*

$$dJ(\Omega; V) = \limsup_{s \rightarrow 0} [J(\Omega_s) - J(\Omega)]/s.
 \tag{59}$$

The form of the directional derivative $dJ_\phi(u; V)$ of the cost functional (36) is given in:

LEMMA 5.1 *The directional derivative $dJ_\phi(u; V)$ of the cost functional (36), for $\phi \in M$ given, at a point $u \in K$ in the direction of vector field V is determined by :*

$$\begin{aligned}
 dJ_\phi(u; V) = & \int_Q [\dot{u}'\eta + \ddot{u}\eta' + (DV(0) + {}^T DV(0))\ddot{u}\eta]dx d\tau + \\
 & \int_\gamma \ddot{u}\eta V(0)n dsdt + \int_Q \sigma'_{ij}e_{kl}(\phi)dxdt + \\
 & \int_\Gamma [(\sigma_{ij}e_{kl}(\phi) - f\phi)V(0)n]ds - \int_{\Gamma_1} (\nabla p\phi V(0) + \\
 & p \nabla \phi V(0) + p\phi D)ds - \int_{\Gamma_2} \sigma'_T\phi_T ds + I_1(u, \phi) - I_2(\lambda, u, \phi),
 \end{aligned}
 \tag{60}$$

where σ' is a shape derivative of the function σ_s with respect to s . This derivative is defined by (40). ∇p is a gradient of function p with respect to x . Moreover $V(0) = V(0, X)$, ϕ_T and σ_T are tangent components of functions ϕ and σ , respectively, as well as D is given by (49).

Proof. Taking into account (36), (39), as well as the formula for transformation of the gradient of the function defined on domain Ω_s into the reference domain Ω , Sokolowski, Zolésio (1992), and using the mapping (29)–(30) we can express

the cost functional (36) defined on domain Ω_s in the form of the functional $J_\phi(u^s)$ defined on domain Ω , determined by:

$$\begin{aligned}
 J_\phi(u^s) = & \int_Q \ddot{u}_s \phi \det D\mathbf{T}_s dx d\tau + \\
 & \int_Q [\sigma_{ij}(D\mathbf{T}_s u^s) e_{kl}(D\mathbf{T}_s \phi_t^s) - f^s \phi] \det D\mathbf{T}_s dx d\tau - \\
 & \int_Q b_{ij} \theta^s e_{ij}(D\mathbf{T}_s \phi) dx d\tau - \\
 & \int_{\gamma_1} p^s \phi \| \det D\mathbf{T}_s^* D\mathbf{T}_s^{-1} n \| ds d\tau - \\
 & \int_{\gamma_2} \lambda_{sT} \phi_T \| \det D\mathbf{T}_s^* D\mathbf{T}_s^{-1} n \| ds d\tau,
 \end{aligned} \tag{61}$$

where $u^s = u_s \circ \mathbf{T}_s \in F$, $u = u_0 \in F$ and $\lambda = \lambda_0 \in \Lambda$. By (59) we have:

$$dJ_\phi(u; V) = \limsup_{t \rightarrow 0} [J_\phi(u^s) - J_\phi(u)]/s. \tag{62}$$

Note that it follows by standard arguments, Haslinger, Neittaanmäki (1988), Myśliński, Tröltzsch (1999), Sokolowski, Zolésio (1992), that the triple $(u_s, \lambda_{sT}, \theta_s) \in K_s \times L_s \times H_s$, $s \in [0, \vartheta)$, $\vartheta > 0$, satisfying the system (32)–(34) is Lipschitz continuous with respect to the parameter s . Passing to the limit with $s \rightarrow 0$ in (62) and taking into account the formulae for derivatives of $D\mathbf{T}_s^{-1}$ and $\det D\mathbf{T}_s$ with respect to the parameter s , Sokolowski, Zolésio (1992), and (40) we obtain (60). ■

In order to eliminate the shape derivatives u', λ', θ' from (60) we introduce an adjoint state $(r, q, p) \in K_2 \times L_2 \times L_3$ defined as follows:

$$\int_Q \ddot{r} \zeta dx d\tau + \int_Q \sigma_{ij}(\zeta) e_{kl}(\phi + r) dx d\tau + \int_{\gamma_2} \dot{\zeta}_T (q - \lambda) \zeta dx d\tau = 0 \quad \forall \zeta \in K_2, \tag{63}$$

with

$$r(T, x) = 0, \quad \dot{r}(T, x) = 0,$$

$$\int_{\gamma_2} (\dot{r}_T + \dot{\phi}_T - \dot{u}_T) \delta dx d\tau = 0, \quad \forall \delta \in L_2, \tag{64}$$

$$\int_0^T \int_\Omega -\frac{\partial p}{\partial t} \varphi dx dt + \int_0^T \int_\Omega \nabla p \nabla \varphi dx dt - \int_0^T \int_{\Gamma_2} \frac{\partial g}{\partial \theta} p \varphi ds dt - \tag{65}$$

$$\int_\Omega \nabla \varphi q dx + \int_\Gamma q \varphi n ds = 0 \quad \forall \varphi \in H, \tag{66}$$

and $p(\mathcal{T}, x) = 0$. Moreover

$$K_2 = \{\zeta \in K_1 : \zeta n = 0 \text{ on } A_0\}, \quad (67)$$

$$L_2 = \{\delta \in \Lambda : \delta = 0 \text{ on } A_0 \cap B_0\}. \quad (68)$$

Since $\phi \in M$ is a given element, then by the same arguments as used to show the existence of solution $(u, \lambda, \theta) \in K \times L \times H$ to the system (32)–(34) we can show the existence of the solution $(r, q, p) \in K_2 \times L_2 \times H$ to the system (63)–(65). From (60), (52), (53), (63), (64) and (65) we obtain

$$dJ_\phi(u; V) = I_1(u, \phi + r) + I_2(\lambda, u, \phi + r) + I_3(u, q - \lambda). \quad (69)$$

The necessary optimality condition has a standard form (see Haslinger, Neittaanmäki, 1988; Hang, Choi, Komkov, 1986; Hlavacek et al., 1986; Sokołowski, Zolésio, 1992):

THEOREM 5.1 *There exists a Lagrange multiplier $\mu \in R$ such that for all vector fields V determined by (29), (30) the following condition holds:*

$$dJ_\phi(u; V) + \mu \int_{\Gamma} V(0)nds \geq 0, \quad (70)$$

where $dJ_\phi(u; V)$ is given by (69).

References

- ADAMS, R.A. (1975) *Sobolev Spaces*. Academic Press, New York.
- CHUDZIKIEWICZ, A. and MYŚLIŃSKI, A. (2002) Augmented Lagrangian Approach for Wheel - Rail Thermoelastic Contact Problem with Friction and Wear. *Preprint*, Systems Research Institute, Warsaw, Poland.
- DUVAUT, G. and LIONS, J.L. (1972) *Les inequations en mecanique et en physique*. Dunod, Paris.
- DENKOWSKI, Z. and MIGÓRSKI, S. (1998) Optimal Shape Design Problems for a Class of Systems Described by Hemivariational Inequalities. *Journal of Global Optimization*, **12**, 37–59.
- ECK, C. and JARUŠEK, J. (1999) The solvability of a Coupled Thermoviscoelastic Contact Problem with Small Coulomb Friction and Linearized Growth of Frictional Heat. *Mathematical Methods in the Applied Sciences*, **22**, 1221–1234.
- GASIŃSKI, L. (2000) An Optimal Shape Design Problem for a Hyperbolic Variational Inequalities. *Discussiones Mathematicae. Differential Inclusions, Control and Optimization*, **20**, 25–31.
- GOELEN, D., MIETTINEN, M., and PANAGIOTOPOULOS, P. (1999) Dynamic Hemivariational Inequalities and Their Applications. *Journal of Optimization Theory and Applications*, **103**, 567–601.

- HAN, W. and SOFONEA, M. (2002) *Quasistatic Contact Problems in Viscoelasticity and Viscoplasticity*. AMS/IP Studies in Advanced Mathematics, **30**.
- HASLINGER, J. and NEITTAANMÄKI, P. (1988) *Finite Element Approximation for Optimal Shape Design. Theory and Application*. John Wiley & Sons.
- HAUG, E.J., CHOI, K.K., and KOMKOV, V. (1986) *Design Sensitivity Analysis of Structural Systems*. Academic Press.
- HLAVACEK, I., HASLINGER, J., NEČAS, J., and LOVISEK, J. (1986) *Solving of Variational Inequalities in Mechanics* (in Russian). Mir, Moscow.
- JARUŠEK, J. (1996) Dynamical Contact Problem with Given Friction for Viscoelastic Bodies. *Czech. Math. Journal*, **46**, 475–487.
- JARUŠEK, J. and ECK, C. (1999) Dynamic Contact Problems with Small Coulomb Friction for Viscoelastic Bodies. Existence of Solutions. *Mathematical Modelling and Methods in the Applied Sciences*, **9**, 11–34.
- JARUŠEK, J., KRBEČ, M., RAO, M., and SOKOŁOWSKI, J. (2002) Conical Differentiability for Evolution Variational Inequalities. To be published in *Journal of Differential Equations*.
- KLABRING, A. and HASLINGER, J. (1993) On almost Constant Contact Stress Distributions by Shape Optimization. *Structural Optimization*, **5**, 213–216.
- MYŚLIŃSKI, A. (1991) Mixed Variational Approach for Shape Optimization of Contact Problem with Prescribed Friction. In: P. Neittaanmäki ed., *Numerical Methods for Free Boundary Problems. International Series of Numerical Mathematics*, Birkhäuser, Basel, **99**, 286 - 296.
- MYŚLIŃSKI, A. (1994) Mixed Finite Element Approximation of a Shape Optimization Problem for Systems Described by Elliptic Variational Inequalities. *Archives of Control Sciences*, **3**, 3–4, 243–257.
- MYŚLIŃSKI, A. (1992) Shape Optimization of Contact Problems Using Mixed Variational Formulation. *Lecture Notes in Control and Information Sciences*. Springer, Berlin, **160**, 414–423.
- MYŚLIŃSKI, A. (2000) Shape Optimization for Dynamic Contact Problems. *Discussiones Mathematicae, Differential Inclusions. Control and Optimization*, **20**, 79–91.
- MYŚLIŃSKI, A. and TRÖLTZSCH, F. (1999) A Domain Optimization Problem for a Nonlinear Thermoelastic System. In: K.H. Hoffmann, G. Leugering, F. Tröltzsch eds., *Optimal Control of PDE. International Series of Numerical Mathematics*, **133**. Birkhäuser, Basel, Switzerland, 221–230.
- NEČAS, J. (1967) *Les Methodes Directes en Théorie des Equations Elliptiques*. Masson, Paris.
- PAWŁOW, I. and ŻOCHOWSKI, A. (2002) Existence and Uniqueness of Solutions for a Three Dimensional Thermoelastic System. *Dissertationes Mathematicae*, **406**, Institute of Mathematics of the Polish Academy of Sciences, Warsaw, Poland.

- SOKOŁOWSKI, J. and ZOLÉSIO, J.P. (1988) Shape sensitivity analysis of contact problem with prescribed friction. *Nonlinear Analysis, Theory, Methods and Applications*, **12**, 1399–1411.
- SOKOŁOWSKI, J. and ZOLÉSIO, J.P. (1992) *Introduction to Shape Optimization. Shape Sensitivity Analysis*. Springer, Berlin.
- TELEGA, J. (1987) Variational Methods in Contact Problems of Mechanics (in Russian). *Advances in Mechanics*, **10**, 3–95.

