

# AN ELASTIC-PLASTIC TORSION OF OPEN PROFILES MADE WITH FUNCTIONALLY GRADED MATERIAL - NUMERICAL EXPERIMENT BASED ON MESHLESS METHODS

A. Uscilowska

*Poznan University of Technology, Poznan, Poland,*

*e-mail: anita.uscilowska@put.poznan.pl*

## 1. Introduction

Elastic-plastic torsion of a bar is an important engineering problem, still discussed in literature. Special class of the bars is under considerations, i.e. we will consider prismatic bars and profiles with open cross-section. Moreover, it is assumed that the bars are made with functionally graded materials.

Twisting of prismatic bars made with homogeneous and isotropic materials have been undertaken by many authors [5; 10; 9; 11]. In the last time, the case of inhomogeneous and/or anisotropic material is more often discussed in literature [2; 3; 12]. It is related to the research of functionally graded materials (FGMs), designed for special engineering applications including aircraft,

aerospace, automobile industry and medicine. Functionally graded materials are characterized by the continuous changes of their properties at least in one direction and this feature distinguishes them from the conventional composite materials [8]. In fact the concept of FGMs is inspired with materials occurring in nature, such as: bones, skin and bamboo [4]. These materials have functionally graded and hierarchical structure and they also have different architecture that results in orthotropic behaviour [1].

In this work the elastic-plastic torsion problem of bars made with FGMs is investigated. In the recent years a number of numerical methods of solving this problem have been developed and improved. It is a more complex issue than problem of elastic bar torsion and proposed numerical methods use different approaches.

## 2. Model of phenomenon

This is a boundary value problem, described by partial differential equation of second order with variable coefficients and appropriate boundary conditions. The problem is formulated for the Prandtl's stress function. Generally, when the shear flexibility modulus is an arbitrary function of cross-sectional coordinates, the analytical solution is not available.

We consider a functionally graded bar of an arbitrary and uniform cross-section. The axis  $Oz$  is parallel to the longitudinal axis of the bar and the bar is twisted by two couples of forces acting on its ends. It is assumed that there are no body forces and the bar is free from external forces on its lateral surface. There are no normal stresses on the frontal cross-section.

In case of functionally graded material characteristic  $G$  in the torsion equation is a shear modulus in all direction axis on the plane whose is normal in direction  $Z$ . The  $G$  is a function of geometrical variables, i.e.  $G(x,y)$ . It is assumed that the  $G(x,y)$  is the continuous and differentiable function depending on geometrical coordinates  $x$  and  $y$ .

The problem is formulated in terms of the Prandtl's stress function and it is described by the equation [7], which is Poisson-like equation. The equation consists of Laplace operator of Prandtl's stress function. In the elastic state the inhomogeneous part of equation is equal to  $-2$ . For plastic state the governing equation consists of Laplace operator and another additional non-linear differential operator of the Prandtl's function. For the formulation the boundary condition has to be described. The boundary condition says that the Prandtl's function is equal to zero on the whole boundary.

The stresses are defined as proper partial derivatives of Prandtl's stress function.

The state of each point of considered cross-section of the bar is estimated by von Mises (Huber) hypothesis, using the stresses given by Prandtl's function.

Moreover, the hardening of the material is taken into account. The hardening phenomenon is described by nonlinear analytical function.

### 3. Meshless methods

The proposal of this paper is to solve problem of elastic-plastic torsion of bar made with FGM using numerical procedure based on one of the meshless methods. The used method is the Fundamental Solution Method (see [6]) supported by approximation by Radial Basis Function. Moreover, the iterative algorithm is applied to treat nonlinearities of the differential equation.

The results of numerical calculation are presented in the paper. The parameters of proposed numerical algorithm are chosen by experiment.

The postprocessing analysis is made, i. e. the stresses and effective plastic stress, effective strain, material flow are calculated and plotted.

The influence of material characteristics and parameters on the torsion, range of plastic deformations are investigated and discussed.

#### References

- [1] V. Birman and L. W. Byrd, Modeling and analysis of functionally graded materials and structures, *Applied Mechanics Reviews* 60:5, 195:216, 2007.
- [2] T. Chen, A novel class of graded cylinders neutral to host shafts of arbitrary cross-sections under torsion, *Mechanics Research Communications* 38:1, 68–71, 2011.
- [3] C. O. Horgan and A. M. Chan, Torsion of functionally graded isotropic linearly elastic bars, *J. Elasticity* 52:2, 181–199, 1998.
- [4] D. K. Jha, T. Kant, and R. K. Singh, A critical review of recent research on functionally graded plates, *Composite Structures* 96, 833–849, 2013.
- [5] J. A. Kołodziej and A. Fraska, Elastic torsion of bars possessing regular polygon in cross-section using BCM, *Computers & Structures* 84:1–2, 78–91, 2005.
- [6] V. D. Kupradze and M. A. Aleksidze, The method of functional equations for the approximate solution of certain boundary value problems. *USSR Comput. Meth. Math. Phys.* 4, 82:126, 1964.
- [7] S. G. Lekhnitskii, *Teori\_ uprugosti anizotropnogo tela*, 2nd ed., Nauka, Moscow, 1977. Translated as *Theory of elasticity of an anisotropic body*, Mir, Moscow, 1981.
- [8] Y. Miyamoto, W. A. Kaysser, B. H. Rabin, A. Kawasaki, and R. G. Ford (editors), *Functionally graded materials: design, processing and applications*, *Materials Technology Series 5*, Springer, New York, 1999.
- [9] A. K. Naghdi, “Torsion of rectangular bars with multiple cylindrical reinforcement or cavities”, *Journal of Applied Mechanics* 61:2, 483–487, 1994.
- [10] W. Nowacki, *Teoria sprężystości*, *Panstwowe Wydawnictwo Naukowe*, Warszawa, 1970.
- [11] S. P. Timoshenko and J. N. Goodier, *Theory of elasticity*, 3rd ed., McGraw-Hill, New York, 1970.
- [12] R. Xu, J. He, and W. Chen, Saint-Venant torsion of orthotropic bars with inhomogeneous rectangular cross section, *Composite Structures* 92:6, 1449–1457, 2010.